

**Service** All Glass Showers has over twenty five years of experience. Customer satisfaction and the care of your home is our number one priority. Our installers will remove their shoes upon entering your home and always use drop sheets in the work area to protect your investment.

**Quality** All Glass Showers, installs frameless shower enclosures without any channels or tracks. We offer our clients the widest range of up to date shower door hardware by CR Laurence the industry leader. We also use only CR Laurence mildew resistant silicone to prolong the life of your shower.

**Valuable Tips** in many cases a little pre planning will enhance the finished project and help save you money at the time of install.

- When tiling your shower stall, be sure to maintain a straight and plumb line where the door and glass will be installed. Marble slabs should be used for best results.
- On knee walls (half walls) these walls must be plumb, especially when the door will be near or mounted on them.
- Half walls should also be 90° angle to threshold at all times
- When designing a Neo-Angle shower enclosure, it is very important to use true angles, i.e. 135° angles
- Shower heads and body sprays should NOT be directed at the shower door, this will cause leaking. ( in some cases seals can be used if it is impossible to direct the shower head away from door )
- Always create a maximum 1/8" slope on the threshold, this will help redirect any water back into the shower enclosure.
- Tempered safety glass panels cannot be less than 4" wide. If a shower door is to be mounted with another piece of glass, the glass panel must be at least 6" wide.
- When designing your shower enclosure, avoid using raised decorative accent tiles around the door opening.
- Glass wall tiles can crack or break, avoid using glass tiles where shower door hinges may be installed, usually hinges are 12" and 60" from threshold.

Call our office for a no obligation quote and check out our website for seasonal saving coupons.